

BAUTECH CD COLOR

THE PRODUCT

Fine decorative overlay cement color to coat concrete floors and walls for indoor and outdoor applications.

FIELDS OF APPLICATION

- Residential floors and walls;
- Commercial and industrial floors and walls;
- Patios;
- Sidewalks;
- Countertops coating;
- Trade Corridors

TECHNICAL SPECIFICATIONS

- Easy application
- Simply mix with water
- Can be applied to a minimum thickness of 5/64 in to 5/32 in (2 mm a 4 mm).
- Provides a great finish in commercial and residential flooring
- Release to light traffic in 48 hours
- No shrinkage and therefore no cracking
- Excellent color stability



SITE PREPARATION

- The cleaning of the substrate is essential for the efficiency of the product. So the site should be completely dry, intact, solid and free of any substance that may hinder the adherence. It is recommended sanding the substrate to remove the small grains on the surface;
- Do not apply on bituminous surfaces such as asphalt and tar.
- For use in new cement bases is necessary to wait for a minimum period of 28 days of curing.

PRODUCT PREPARATION

- Mix the contents of BAUTECH CD COLOR, to 0,26 gallons (1.0 liter) of clean water in a bucket (metal or plastic).

APPLICATION

- The first step is for the primer layer: moisten the substrate and applying the product as a primer layer with trowel at an angle of 45 ° relative to the base. This promotes a thin sealer layer into the pores.
- Wait about 50 minutes before proceeding to the next step.
- Sanding and moisten the base again and apply a second coat, regulating and leveling.
- Wait about 40 minutes and then proceed to the stage of finishing.
- To velvety finish, use a damp sponge and lightly press against the application, in circular motions.
- If you prefer the stained finish, use a flat metal trowel and press lightly against the application, in circular motions;
- Consider the minimum thickness of 5/64 in to 5/32 in (2mm to 4mm);
- Existing joints must be respected;
- If rest any doubt, please check technical and application details previously with the Technical Department of BAUTECH, by e-mail (sac@bautechbrasil.com.br)



PRECAUTIONS

- *Keeping the closed container when not in use.*
- *Never reuse the packaging for any purpose other than the conditioning of the product.*
- *Store the original packaging in a dry, ventilated area away from heat sources.*
- *Keep out of reach of children and pets.*
- *Prepare and apply the product to the ever-drying ventilated area.*
- *We recommend the use of PPE (personal protective equipment) such as gloves, boots and goggles.*
- *In case of contact with skin and eyes, rinse with clean running water for 45 minutes. If swallowed, do not induce vomiting. In both cases, consult a doctor immediately and take the pack.*

WARRANTY

The information contained herein is supported by tests, analyzes and technical knowledge. Measured values and results may fluctuate due to environmental characteristics and / or use of the product that are not manufacturer's responsibility. There is no other express or implied warranties. No agent, seller, distributor or dealer has the authority to extend, modify or suppress these provisions.

LIMITATIONS

- *Apply only on cement bases (common subfloor)*
- *Do not use when the substrate temperature is, or will be in the next few hours, below 59°F (15°C) or above 100°F (38°C).*